



Scan Here For More Info



H 5101 - Safety Gloves

EN 388:2016

STANDARD :



4544D

INDUSTRY

Petrochemical

Automotive

Glass

Metal structure
construction

Machinery & equipment's

IDEAL APPLICATIONS

General handling

Heavy material handling

General manual jobs

Assembly, Machining /
Stamping / Cutting

Raw material handling

SPECIAL FEATURES



OILY ENVIRONMENT



GRIP



ABRASION



CUT-RESISTANT



DEXTERITY

LINER TYPE	COATING	ADVANTAGE
UHMWPE liner	Flat nitrile & sandy nitrile	Cut and liquid resistance with high dexterity

LINER COLOUR	COATING COLOUR	COATING TYPE	SIZE	CUFF	CERTIFICATION
Salt pepper	Blue / Black	3/4 th flat nitrile & palm sandy nitrile	8 & 9	Normal overlocked	EN388 : 2016 – 4544D

FEATURES

UHMWPE (ultra high molecular weight polyethylene)
cut level 5 / D liner

3/4th flat nitrile & palm sandy nitrile

Coating will give high level of liquid / semi-liquid permeation
protection and liner will provide cut level 5 / D protection

Seamless knitted liner for ultimate comfort and higher flexibility

APPLICATION

Assembly line, assembling metal parts and components

Handling sharp or irregular metal pieces

Press shop, scrap handling, hardware assembly etc

STORAGE

Store in cool and dry place

Do not store in direct / high heat or sunlight

Can be stored and transported in their original cartons

LAUNDERABLE

Yes (as per instruction)

PACKING

120 pairs
per cartoon

Udyogi Plastics Private Limited

294, B. B. Ganguly Street,
2nd Floor, Kolkata - 700 012

E-mail : info@udyogi.net

Website : www.udyogisafety.com

Tel. : +91 33 2225 1470/71/72