



EDGE RAPID

Microfiber Safety Shoe

STANDARD : IS : 15298-Part 2 TYPE : I , DESIGN : B

INDUSTRY

Logistics & Transports	Petro-Chemicals
Oil & Gas	Elevators ,Construction

SPECIAL FEATURES

TOE CAP	ANTI-SKID	PUNCTURE RESISTANCE	ANTISTATIC	ODOUR LESS	WATER RESISTANCE



COMPONENT	MATERIAL	ADVANTAGE
Upper	Microfiber with Reflector	Nubuck finish with Reflector for low light area
Lining	Breathable Mesh with foam padded 200gsm	Keeps the foot warm & dry and balance the moisture inside the shoe
Toe Cap	Composite toe 200 J	Light weight protective reinforcement in the toe which protects the foot from falling object
Sole	Double density Polyurethane (PU)	Antistatic ,Resistance to slip and bending performance, Direct Injection Molded Cleated sole with Extended Toe Guard
Insocks	Extra Comfort PU	Improved shock absorption, prevent jerk, ankle & leg injuries, Extra comfortable work

COLLAR	TONGUE	EYELET	LACE	THREAD	WEIGHT
Foam padded	Foam padded	Non Metallic	Round Nylon	Nylon 3/6 ply	1100 gms for size-8 with tolerance of $\pm$ 5% for all sizes

FEATURES	APPLICATION		
Very good physical & chemical properties	Transport : Automotive / Aerospace		
High tear & tensile endurance	IT & Technology - Telecom, Production Process		
Complete Metal free Design	Oil & Gas, Construction		
Metal free Penetration resistance insole			
Slip resistance sole-SRC			
Heat Resistant Sole upto 130°C			
Cleated sole with Ladder Grip			
Antistatic Double Density DIP PU Sole			
Water resistance Upper			
Anti-bacterial & Odor free			
Composite toe cap - 200 J impact resistance			
	STORAGE		
	Store away from sunlight, at room temperature		
	Keep in a dry, well ventilated space		
	Keep in cleaned and ready to be used condition		
	PACKING	SIZE	CLEANING
	10 pairs per carton	5 to 12	Wipe with a soft cotton cloth, soaked in warm water and mild liquid soap. Dry it in shaded & ventilated place.

Udyogi