



EDGE LSD

Microfiber Safety Shoe

STANDARD : IS : 15298-Part 2

INDUSTRY

Logistics & Transports	Hotel, Production Process
Automotive	Electronics, Fertilizers

SPECIAL FEATURES

TOE CAP	ANTI-SKID	ANTI-BACTERIAL	ANTISTATIC	ODOUR LESS	WATER RESISTANCE



COMPONENT	MATERIAL	ADVANTAGE
Upper	Microfiber	Water Resistance upper
Lining	Cambrelle with foam padded 200gsm	Keeps the foot warm & dry and balance the moisture inside the shoe
Toe Cap	Alloy Steel toe -200 J	Protective reinforcement in the toe which protects the foot from falling object
Sole	Double density Polyurethane (PU/PU)	Antistatic, Resistance to slip and bending performance, DIP PU Cleated sole with Extended toe guard
Insocks	Extra Comfort PU	Improved shock absorption, prevent jerk, ankle & leg injuries. Extra comfortable work

COLLAR	TONGUE	EYELET	LACE	THREAD	WEIGHT
Foam padded	Foam padded	-	-	Nylon 3/6 ply	825 gms for size-5 with tolerance of $\pm$ 5% for all sizes

FEATURES	APPLICATION		
Very good physical & chemical properties	Transport : Automotive / Aerospace		
Reflector for low light area	IT & Technology - Telecom, Production Process		
Excellent resistance to abrasion	Oil & Gas, Construction, Chemical and food		
Excellent breathability			
Slip resistance sole-SRC			
Cleated sole with Ladder grip			
Ease of care			
Antistatic PU Double Density Sole			
Water resistance upper			
Anti-bacterial & Odor free			
Alloy Steel toe cap - 200 J impact resistance			
	STORAGE		
	Store away from sunlight, at room temperature		
	Keep in a dry, well ventilated space		
	Keep in cleaned and ready to be used condition		
	PACKING	SIZE	CLEANING
	10 pairs per carton	2 to 10	Wipe with a soft cotton cloth, soaked in warm water and mild liquid soap. Dry it in shaded & ventilated place.

Udyogi