



EDGE ESD

Microfiber Safety Shoe

STANDARD : IS : 15298-Part 2 TYPE : I , DESIGN : A

INDUSTRY

Electronics	Petro-Chemicals
Oil & Gas	Pharma

SPECIAL FEATURES

TOE CAP	ANTI-SKID	ANTI-BACTERIAL	ESD	ODOUR LESS	WATER RESISTANCE



COMPONENT	MATERIAL	ADVANTAGE
Upper	Microfiber Plain	Excellent resistance to hydrolysis, abrasion etc.
Lining	Cambrelle with foam padded 200gsm	Keeps the foot warm & dry and balance the moisture inside the shoe
Toe Cap	Alloy Steel toe	Protective reinforcement in the toe which protects the foot from Impacts up to 200 J and compression up to 15kn.
Sole	Double density Polyurethane (PU)	Resistance to slip and bending performance, Direct Injection Molded Cleated sole with Extended Toe Guard
Insocks	Perforated EVA	Improved shock absorption, prevent jerk, ankle & leg injuries. Extra comfortable work

COLLAR	TONGUE	EYELET	LACE	THREAD	WEIGHT
Foam padded	Foam padded	Round metal	Round Nylon Black	Nylon 3/6 ply	1100 gms for size-8 with tolerance of $\pm 5\%$ for all sizes

FEATURES	APPLICATION
Suitable for use in ESD sensitive area	Transport : Automotive / Aerospace
High tear & tensile endurance	IT & Technology - Telecom, Production Process
Excellent resistance to abrasion	Oil & Gas, Pharma
Excellent breathability	
Slip resistance sole-SRC	
Heat Resistant Sole upto 130°C	
Cleated sole with Ladder Grip	
Anti-Static(ESD) In the range of 0.1 to 100 MΩ	
Water Resistance Upper	
Anti-bacterial & Odor free	
Alloy Steel toe cap - 200 J impact resistance	
	STORAGE
	Store away from sunlight, at room temperature
	Keep in a dry, well ventilated space
	Keep in cleaned and ready to be used condition
	PACKING
	10 pairs per carton
	SIZE
	5 to 12
	CLEANING
	Wipe with a soft cotton cloth, soaked in warm water and mild liquid soap. Dry it in shaded & ventilated place.

Udyogi