UDYOGI®
LIFE IS PRECIOUS

Scan Here For More Info

INDUSTRY	IDEAL APPLICATIONS
Construction & infrastructure	-
Metal & steel	-
Heavy engineering	-
Production process	-
Chemical industry	-

TANGO IMPACT - Safety Shoe
Industrial safety shoe

STANDARD : IS : 15298-Part 3

SPECIAL FEATURES

TOE CAP | ANTI-SKID | ANTI-BACTERIAL | CLEATED SOLE | ODOUR LESS | SLIP RESISTANCE

COMPONENT	MATERIAL	ADVANTAGE
Upper	Barton print Synthetic Leather	Excellent tensile & tear strength, durability, breathability, etc.
Lining	Synthetic with foam padded	Keeps the foot warm & dry and balance the moisture inside the shoe
Toe Cap	Alloy steel	Protective reinforcement in the toe which protects the foot from falling objects
Sole	Soft Polymer Injected	Resistance to slip, chemicals, acid, alkali & heat resistance upto 150° cel. for 01 minute
Insocks	EVA with textile	Improve shock absorption, provides pain relief, ankle & leg injuries with extra comfort

COLLAR	TONGUE	EYELET	LACE	THREAD	WEIGHT
Foam padded	Foam padded	Coated Aluminium	Nylon	Nylon 3/6 ply	1150 gms for size-8 with tolerance of ± 5% for all sizes

FEATURES
Very good physical & chemical properties
High tear & tensile strength
Excellent resistance to abrasion
Excellent breathable Lining
Ageing resistance
Durability
Ease of care
Light weight
Water Resistance upper
Anti-bacterial & no odours
Steel toe cap - 100 J

APPLICATION
Construction & infrastructure
Warehouse & transport
Manufacturing - All types of small manufacturing industries
Service industry

STORAGE
Store in a dark, dry & well ventilated area
Keep away from sources of heat
Keep shoe of the floor

CLEANING	SIZE	PACKING
Wipe with a damp cloth to remove dirt & dust and after that polish with black cherry cream	5 to 12	20 pairs per carton

Udyogi Plastics Private Limited

294, B. B. Ganguly Street,
2nd Floor, Kolkata - 700 012

E-mail : info@udyogi.net
Website : www.udyogisafety.com

Tel. : +91 33 2225 1470/71/72