



EDGE AERO

Microfiber Safety Shoe

STANDARD : IS : 15298-Part 2

INDUSTRY

Logistics & Transports	Production Process
Automotive	Electronics

SPECIAL FEATURES

TOE CAP	ANTI-SKID	PUNCTURE RESISTANCE	ANTISTATIC	ODOUR LESS	METAL FREE



COMPONENT	MATERIAL	ADVANTAGE
Upper	Suede Microfiber + Mesh	Excellent resistance to hydrolysis, abrasion etc.
Lining	Breathable Mesh with foam padded 200gsm	Keeps the foot warm & dry and balance the moisture inside the shoe
Toe Cap	Composite -200 J	Protective reinforcement in the toe which protects the foot from falling object
Sole	Double density Polyurethane (PU)	Antistatic, Resistance to slip and bending performance, DIP PU Cleated sole with Extended toe guard
Insocks	Extra Comfort PU Molded	Improved shock absorption, prevent jerk, ankle & leg injuries. Extra comfortable work

COLLAR	TONGUE	EYELET	LACE	THREAD	WEIGHT
Foam padded	Foam padded	Reflective Loops	Reflective Nylon	Nylon 3/6 ply	1050 gms for size-8 with tolerance of $\pm 5\%$ for all sizes

FEATURES	APPLICATION		
Complete Metal free -Airport Friendly	Transport : Automotive / Aerospace		
High tear & tensile endurance	IT & Technology - Telecom, Production Process		
Antistatic 100kΩ to 1000MΩ	Logistics, Construction		
Excellent breathability			
Slip resistance sole-SRC			
Cleated sole with Ladder grip			
Metal free Penetration Resistance -1100 N			
Scuff protection Sole design			
Reflective Inserts on Upper for low light area			
Anti-bacterial & Odor free			
Composite toe cap - 200 J impact resistance			
STORAGE			
Store away from sunlight, at room temperature			
Keep in a dry, well ventilated space			
Keep in cleaned and ready to be used condition			
PACKING	SIZE	CLEANING	
10 pairs per carton	5 to 12	Wipe with a soft cotton cloth, soaked in warm water and mild liquid soap. Dry it in shaded & ventilated place.	

Udyogi