



TECHNICAL DATA SHEET

117P-RB

Sandy Nitrile Cut Level 1 Gloves.

Product Introduction:

- The 117P-RB glove is designed for optimal hand protection in dry and slightly oily environments. It features a 13-gauge seamless red polyester liner for comfort and breathability, paired with a black sandy nitrile palm coating for superior grip and durability.



Features:

- Liner:** 13-gauge seamless red polyester
- Coating:** Black Sandy Nitrile (Palm Coated)
- Cuff:** Elastic knit wrist for a snug fit
- Design:** Ergonomic and lightweight construction for extended wear

Product Specifications:

Materials Of Liner: Polyester
Liner color; Red
Gauge Of Liner Yarn: 13-Gauge
Coating Material: Sandy Nitrile/ Single Dip
Color Coating: Black
CE Rating: EN 388: 2016 4131
Sizes Available: 8-9

Performance – EN 388:2016

EN 388 : 2016 – 4131

Test	Performance Level
Abrasion Resistance	4
Cut Resistance (Coup Test)	1
Tear Resistance	3
Puncture Resistance	1

Industry :

These Gloves are utilized for their protective and practical features in various industries such as



General Maintenance
& Assembly



Packaging &
Logistics



Handling dry &
slightly oily parts



Light Construction
work

Udyogi



Advantages of Sandy Nitrile Coating:

- Excellent grip performance, especially in dry and oily conditions
- High abrasion resistance for extended glove life
- Durable and flexible coating maintains dexterity
- Oil-repellent texture for better handling of slick surfaces

Usage Instructions :

- Insert hand fully and align fingers properly
- Do not pull forcefully to remove.
- Inspect before and after use for damage.
- Not suitable for high-heat or chemical exposure tasks.

Washing Instructions:

- Hand-wash with mild detergent.
- Do not bleach, iron, or tumble dry.
- Air dry completely before reuse.

Storage:

- Store in a cool, dry place below 40°C.
- Avoid exposure to direct sunlight and high humidity.
- Shelf life: 3 years from the date of manufacture under recommended storage conditions.