



## EDGE MARSHAL

### Microfiber Safety Shoe

STANDARD : IS : 15298-Part 2

#### INDUSTRY

|                        |                           |
|------------------------|---------------------------|
| Logistics & Transports | Hotel, Production Process |
| Automotive             | Electronics, Fertilizers  |

#### SPECIAL FEATURES

|         |           |                |            |            |                  |
|---------|-----------|----------------|------------|------------|------------------|
|         |           |                |            |            |                  |
| TOE CAP | ANTI-SKID | ANTI-BACTERIAL | ANTISTATIC | ODOUR LESS | WATER RESISTANCE |



| COMPONENT | MATERIAL                                | ADVANTAGE                                                                                           |
|-----------|-----------------------------------------|-----------------------------------------------------------------------------------------------------|
| Upper     | Microfiber with Reflector               | Water Resistance upper with reflector                                                               |
| Lining    | Breathable Mesh with foam padded 200gsm | Keeps the foot warm & dry and balance the moisture inside the shoe                                  |
| Toe Cap   | Alloy Steel toe -200 J                  | Protective reinforcement in the toe which protects the foot from falling object                     |
| Sole      | Double density Polyurethane (PU/PU)     | Antistatic, Resistance to slip and bending performance, DIP PU Cleated sole with Extended toe guard |
| Insocks   | Perforated EVA                          | Improved shock absorption, prevent jerk, ankle & leg injuries. Extra comfortable work               |

| COLLAR      | TONGUE      | EYELET       | LACE  | THREAD        | WEIGHT                                                        |
|-------------|-------------|--------------|-------|---------------|---------------------------------------------------------------|
| Foam padded | Foam padded | Coated round | Nylon | Nylon 3/6 ply | 1050 gms for size-8 with tolerance of $\pm 5\%$ for all sizes |

| FEATURES                                      | APPLICATION                                    |         |                                                                                                                |
|-----------------------------------------------|------------------------------------------------|---------|----------------------------------------------------------------------------------------------------------------|
| Very good physical & chemical properties      | Transport : Automotive / Aerospace             |         |                                                                                                                |
| Reflector for low light area                  | IT & Technology - Telecom, Production Process  |         |                                                                                                                |
| Excellent resistance to abrasion              | Oil & Gas, Construction, Chemical and food     |         |                                                                                                                |
| Excellent breathability                       |                                                |         |                                                                                                                |
| Slip resistance sole-SRC                      |                                                |         |                                                                                                                |
| Cleated sole with Ladder grip                 |                                                |         |                                                                                                                |
| Ease of care                                  |                                                |         |                                                                                                                |
| Antistatic PU Double Density Sole             |                                                |         |                                                                                                                |
| Water resistance upper                        |                                                |         |                                                                                                                |
| Anti-bacterial & Odor free                    |                                                |         |                                                                                                                |
| Alloy Steel toe cap - 200 J impact resistance |                                                |         |                                                                                                                |
|                                               | STORAGE                                        |         |                                                                                                                |
|                                               | Store away from sunlight, at room temperature  |         |                                                                                                                |
|                                               | Keep in a dry, well ventilated space           |         |                                                                                                                |
|                                               | Keep in cleaned and ready to be used condition |         |                                                                                                                |
|                                               | PACKING                                        | SIZE    | CLEANING                                                                                                       |
|                                               | 10 pairs per carton                            | 5 to 12 | Wipe with a soft cotton cloth, soaked in warm water and mild liquid soap. Dry it in shaded & ventilated place. |

Udyogi