



TECHNICAL DATA SHEET

ADG470ONJ FR Jacket

All Day Garment 470 GSM Jacket

PRODUCT INTRODUCTION

ADG Treated Flame Retardant (FR) work wear are a crucial element of personal protective equipment (PPE) designed to safeguard workers in environments where exposure to molten metal, flames, heat hazards is a risk. FR workwear are made from the fabric that combines the natural properties of cotton with additional treatments to enhance its flame resistance. The fabric undergoes a treatment to make it resistant to flames. This means it won't ignite easily, and if it does catch fire, it will self-extinguish quickly, reducing the risk of burns. This makes them a reliable choice for industries such as molten metal (Iron, Steel), oil and gas, electrical utilities, and other sectors where flash fire hazards are prevalent.



SPECIAL FEATURES



FR



WASHABLE



LIGHT WEIGHT



FLEXIBLE



BREATHABLE



DURABLE



SKIN FRIENDLY



QUALITY PRODUCT

COLOUR



Orange



Navy Blue

STYLE	FABRIC COMPOSITION	PPE CATEGORY	TRIM	MARKING
Jackets	100% Cotton Treated Flame Retardant Woven Fabric (470 gsm-13.86 oz) ±5%	ATPV Rating -24 cal/cm ² Cat-II	100% FR Thread Plastic Snap Button FR Reflective Piping	Manufacturer Logo, Model No., Fabric Composition, Certification, Size, Washcare Instruction

FEATURES

- Skin friendly fabric
- Protection against molten iron
- Protect against thermal effects of an ARC Flash
- FR performance will remain same till the last washing cycle
- The hi-tech fabric will not cause any itchiness & stiffness

APPLICATION

- Blust Furnace
- Steel Melting Shop
- Platemill
- Raw Material Handling System
- Slag Remove and Coking Plant

STORAGE

- May be stored in the dark for upto 2 years
- Do not store in direct/high heat or sunlight at this may distort the properties of the fabric
- Can be stored and transported in their original cartons at ambient temperature

DESIGN

- Turn down collar, waist adjustment with velcro
- FR silver reflective piping on chest and sleeves
- 2 chest pockets with flap and velcro closing
- Front closer with plastic snap button and velcro, cuff closer with plastic snap button

CLEANING	PACKING	AVAILABLE SIZES
Use light detergent for gentle wash	1 pc per packet	S, M, L, XL, XXL, XXXL

Udyogi



CERTIFICATIONS

 **EN ISO 11612** Specifies performance requirements for protective clothing made from flexible materials, which are designed to protect the wearer's body from heat and/or flame, describe in below chart:

EN ISO 11612:2015

CODE	INSPECTION CHARACTERISTIC	STANDARD	LEVELS
A	Limited Flame Spread, Surface Ignition	ISO 15025	1 (Lowest 2, Highest 1)
	Edge Ignition		2 (Lowest 2, Highest 1)
B	Convective Heat	ISO 9151	1 (Lowest 1, Highest 3)
C	Radiant Heat	ISO 6942	1 (Lowest 1, Highest 4)
E	Molten Iron	ISO 9185	3 (Lowest 1, Highest 3)
F	Contact Heat	ISO 12127	2 (Lowest 1, Highest 3)



Test method used to calculate quantitative results (arc ratings) for FR fabrics. Arc ratings are a measure of thermal protection provided by the fabric in an arc flash.



To protect personnel by reducing exposure to major electrical hazards. It helps to avoid workplace injuries and fatalities due to shock, electrocution, arc flash, and arc blast.



The above mentioned goods meet the Human-Ecological requirements of the STANDARD 100 by Oeko-Tex presently in ANNEX 4 for products direct contact to skin.

INDUSTRY



Iron & Steel



Metals & Mining



Material Handling



Cement



Machinery & Equipment



Energy & Power



Automotive



Pharmaceutical



Automobile

WASHING INSTRUCTIONS

- Wash at maximum 60°C
- Never use chlorine bleach
- Use liquid detergents only
- Do not iron
- Do not dry clean
- Tumble dry at low heat
- Wash in an industrial washer





ADG4700NJ FR Jacket



FR JACKET SIZE CHART

SIZE	S	M	L	XL	2XL	3XL
LENGTH	26"1/4	27"1/4	28"1/4	29"1/4	30"1/4	31"1/4
CHEST ROUND	46"	47"	48"	50"	51"	52"
SHOULDER	18"1/2	19"1/2	20"1/2	21"1/2	22"1/2	23"1/2
SLEEV LENGTH	24"1/2	25"	25"1/2	26"	26"1/2	27"

Udyogi