



Scan Here For More Info



TANGO DD
Microfiber Safety Shoe

STANDARD : IS : 15298 : PART-2 :2016

IDEAL INDUSTRY

Heavy Engineering

Construction

Metal

Logistics

Production Process

SPECIAL FEATURES



ANTI-BACTERIAL



ANTI-SKID



WATER RESISTANCE



ODOUR LESS



TOE CAP

COMPONENT	MATERIAL	ADVANTAGE
Upper	Microfiber Plain	Excellent resistance to hydrolysis, abrasion etc.
Lining	Spacer with foam padded -200 gsm	Keeps the foot warm & dry and balance the moisture inside the shoe
Toe Cap	Alloy Steel 200 J	Protective reinforcement in the toe which protects the foot from falling objects
Sole	PU - Double Density	Double density high abrasion resistance, resistance to hot contact, slip & bending performance, shock absorber, mild, chemicals
Insocks	3mm Eva Laminated	Improve shock absorption, provides pain relief, ankle & leg injuries with extra comfort

COLLAR	TONGUE	EYELET	LACE	THREAD	WEIGHT
Foam padded	Foam padded	Round coated rust free	Dual Color Nylon	Nylon 3/6 ply	980 gms with tolerance of $\pm 5\%$ for Size 8

FEATURES

Very good physical & chemical properties

High tear & tensile strength

Excellent resistance to abrasion

Excellent breathability

Ageing resistance

Durability

Slip Resistance Level SRC

Light weight

Water repellent

Anti-bacterial & no odours

Alloy steel toe cap - 200J

APPLICATION

Automotive

Logistics, Production Process, Service Industry

Construction , Heavy Metal

STORAGE

Store in a dark, dry & well ventilated area

Keep away from sources of heat

Keep shoe of the floor

CLEANING

With a mixture of warm water & mild liquid soap & wipe them down with a damp cloth to remove dirt & dust

PACKING

20 pairs per carton