



TECHNICAL DATA SHEET

MT330NRJ
D3E3 Jacket

Metprotek D3E3 IFR 330 gsm Jacket

PRODUCT INTRODUCTION

Metprotek Inherently Flame Retardant (IFR) Jacket are a crucial element of personal protective equipment (PPE) designed to safeguard workers in environments where exposure to molten metal, flames, heat, and flash fire hazards is a risk. IFR Jacket are made from the fabric that have built-in flame-resistant properties that do not wash or wear out over time. This makes them a reliable choice for industries such as molten metal (aluminium, zinc, iron), oil and gas, electrical utilities and other sectors where fire hazards are prevalent.



SPECIAL FEATURES

							
IFR	WASHABLE	LIGHT WEIGHT	FLEXIBLE	BREATHABLE	DURABLE	SKIN FRIENDLY	QUALITY PRODUCT

COLOUR

	Red
	Navy Blue

STYLE	FABRIC COMPOSITION	TRIM	MARKING
Jacket	100% Inherent Flame Retardant Fabric 330-340 gsm (FR Viscose/ Wool/ Nylon) ±5%	100% Meta-Aramid Thread FR Velcro FR Snap Button	Manufacturer Logo, Model No, Washcare Instruction, Certification, Fabric Composition, Size

FEATURES

- Skin friendly fabric
- Protection against molten iron
- Protect against thermal effects of an ARC Flash
- FR performance will remain same till the last washing cycle
- The hi-tech fabric will not cause any itchiness & stiffness

APPLICATION

- Blust Furnace
- Steel Melting Shop
- Platemill
- Raw Material Handling System
- Slag Remove and Coking Plant

STORAGE

- May be stored in the dark for upto 2 years
- Do not store in direct/high heat or sunlight at this may distort the properties of the fabric
- Can be stored and transported in their original cartons at ambient temperature

DESIGN

- High collar
- Front closing with flap & plastic cross button
- 2" FR silver reflective tape on chest and sleeves
- Cuff adjustment with snap button
- 2 Bone pockets & Waist adjustment with velcro

CLEANING	PACKING	AVAILABLE SIZES
Use light detergent for gentle wash	1 pc per packet	S, M, L, XL, XXL, XXXL

Udyogi



CERTIFICATIONS



EN ISO 11612:2015

Specifies performance requirements for protective clothing made from flexible materials which are designed to protect the wearer's body from heat and/or flame, describe in below chart:



EN ISO 11612:2015

CODE	INSPECTION CHARACTERISTIC	STANDARD	LEVELS
A	Limited Flame Spread, Surface Ignition	ISO 15025	1 (Lowest 2, Highest 1)
	Edge Ignition		2 (Lowest 2, Highest 1)
B	Convective Heat	ISO 9151	1 (Lowest 1, Highest 3)
C	Radiant Heat	ISO 6942	1 (Lowest 1, Highest 4)
D	Molten Aluminium	ISO 9185	3 (Lowest 1, Highest 3)
E	Molten Iron	ISO 9185	3 (Lowest 1, Highest 3)
F	Contact Heat	ISO 12127	1 (Lowest 1, Highest 3)



EN ISO 11611:2015

Test method specifies the minimum safety requirements for protective clothing for welding and allied processes.



IEC 61482:2020

The overall standard that covers protective clothing against the thermal arc hazards of an electric arc.



ELIM

Indicates the energy level to which the garment may be exposed with a 0% risk of second-degree burn (ATPV and EBT indicate a 50% risk of a burn).



EN 1149-5:2018

Test method for materials to be used in the production of protective clothing with electrostatic dissipation for preventing incendiary discharge.



EN ISO 13688 : 2013_A1 : 2021

Specifies general performance requirements for ergonomics, innocuousness, size designation, ageing, compatibility and marking of protective clothing and the information to be supplied by the manufacturer with the protective clothing.



ISO EN ISO 14362-1:2017

Describes a method to detect the use of certain azo colorants that may not be used in the manufacture or treatment of certain commodities made of textile fibres and that are accessible to reducing agent with and without extraction.



The above mentioned goods meet the Human-Ecological requirements of the STANDARD 100 by Oeko-Tex presently in ANNEX 4 for products direct contact to skin.

INDUSTRIES



Aluminium



Steel



Zinc



Copper



Oil & Gas




Automotive



Aerospace

WASHING INSTRUCTIONS

- Wash at maximum 60°C
- Never use chlorine bleach
- Use liquid detergents only
- Do not iron
- Do not dry clean
- Tumble dry at low heat
- Wash in an industrial washer



Udyogi



MT330NRJ
D3E3 Jacket



JACKET SIZE CHART

SIZE	S	M	L	XL	2XL	3XL
LENGTH	26"1/4	27"1/4	28"1/4	29"1/4	30"1/4	31"1/4
CHEST ROUND	46"	47"	49"	50"	51"	52"
SHOULDER	18"1/2	19"1/2	20"1/2	21"1/2	22"1/2	23"1/2
SLEEVE LENGTH	24"1/2	25"	25"1/2	26"	26"1/2	27"

Udyogi